

Ceramic Bandpass Filter 50Ω

ZBA-34C-2300BW200B



■ Features

- ROHS Compliant
- High power rating
- High rejection

■ Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	2300	-	2300	-	MHz
Bandwidth	200	2200	-	2400	MHz
Insertion Loss	2200 ~ 2400	-	1.5	2.0	dB
Ripple		-	0.3	0.5	dB
Return Loss		15.0	17.0	-	dB
Attenuation	2000	30.0	33.0	-	dB
	3000	50.0	53.0	-	dB
	4000 ~ 4500	45.0	50.0	-	dB
	-	-	-	-	-
	-	-	-	-	-

■ Maximum Ratings


Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

■ Dimension



■ PCB Layout



For product information and a complete list of distributors, please go to our website

address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954

Tel : +82-31-8025-7100

Fax : +82-31-8025-7200



www.zenix08.com

Ceramic Bandpass Filter 50Ω

ZBA-34C-2300BW200B

Typical Performance Data at 25°C

- Insertion Loss, Ripple, Return Loss, Attenuation



For product information and a complete list of distributors, please go to our website

address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954

Tel : +82-31-8025-7100

Fax : +82-31-8025-7200

www.zenix08.com