

# Ceramic Bandpass Filter 50Ω

ZBA-45C-1120BWST



### Features

- ROHS Compliant
- High power rating
- High rejection

### Pricing

Quantity	Unit Price
1 ~ 10	₩ 52,000
11 ~ 24	₩ 49,000
25 ~ 49	₩ 44,000
50 ~ 99	₩ 38,000
100 ~	₩ 28,000

### Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	1120	-	1120	-	MHz
Bandwidth	Single Tone	-	-	-	MHz
Insertion Loss	1120	-	3.5	4.5	dB
Ripple		-	-	-	dB
Return Loss		15.0	17.0	-	dB
Attenuation	DC ~ 1000	60.0	70.0	-	dB
	1080	55.0	58.0	-	dB
	1160	43.0	46.0	-	dB
	2240	60.0	75.0	-	dB
	-	-	-	-	-

### Maximum Ratings


Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

### Dimension



### PCB Layout



For product information and a complete list of distributors, please go to our website

[www.zenix08.com](http://www.zenix08.com)


address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954

Tel : +82-31-8025-7100

Fax : +82-31-8025-7200

## Typical Performance Data at 25°C

- Insertion Loss, Ripple, Return Loss, Attenuation



- Attenuation

