

Ceramic Bandpass Filter 50Ω

ZBA-45C-2720BW80C



Features

- ROHS Compliant
- High power rating
- High rejection

Pricing

Quantity	Unit Price
1 ~ 10	₩ 52,000
11 ~ 24	₩ 49,000
25 ~ 49	₩ 44,000
50 ~ 99	₩ 38,000
100 ~	₩ 28,000

Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	2720	-	2720	-	MHz
Bandwidth	80	2680	-	2760	MHz
Insertion Loss	2680 ~ 2760	-	2.0	3.0	dB
Ripple		-	0.7	1.0	dB
Return Loss		15.0	17.0	-	dB
Attenuation	1360	65.0	70.0	-	dB
	4080	65.0	70.0	-	dB
	5440 ~ 5600	40.0	50.0	-	dB
	-	-	-	-	-
	-	-	-	-	-

Maximum Ratings


Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

Dimension



PCB Layout



For product information and a complete list of distributors, please go to our website

www.zenix08.com


address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954

Tel : +82-31-8025-7100

Fax : +82-31-8025-7200

▣ Typical Performance Data at 25°C

- Insertion Loss, Ripple, Return Loss, Attenuation



- Attenuation

