

Ceramic Bandpass Filter 50Ω

ZBA-46R-880BW160B



Features

- ROHS Compliant
- High power rating
- High rejection

Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	880	-	880	-	MHz
Bandwidth	160	800	-	960	MHz
Insertion Loss	800 ~ 960	-	1.5	2.0	dB
Ripple		-	0.4	0.5	dB
Return Loss		15.0	16.0	-	dB
Attenuation	DC ~ 560	65.0	70.0	-	dB
	750	15.0	20.0	-	dB
	1700	65.0	70.0	-	dB
	-	-	-	-	-
	-	-	-	-	-

Maximum Ratings


Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

- Permanent damage may occur if any of these limits are exceeded.

Dimension



PCB Layout



RF&MICROWAVE TOTAL SOLUTION

For product information and a complete list of distributors, please go to our website

address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954


Tel : +82-31-8025-7100

Fax : +82-31-8025-7200

www.zenix08.com

Typical Performance Data at 25°C

- Insertion Loss, Ripple, Return Loss, Attenuation



- Attenuation

