



▣ Features

- ROHS Compliant
- High power rating
- High rejection

▣ Pricing

Quantity	Unit Price
1 ~ 10	₩ 72,000
11 ~ 24	₩ 68,000
25 ~ 49	₩ 62,000
50 ~ 99	₩ 52,000
100 ~	₩ 39,000

▣ Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	2647.5	-	2647.5	-	MHz
Bandwidth	25	2635	-	2660	MHz
Insertion Loss	2635 ~ 2660	-	2.5	3.0	dB
Ripple		-	0.5	1.0	dB
Return Loss		15.0	17.0	-	dB
Attenuation	2577.5	60.0	65.0	-	dBc
	-	-	-	-	-
	-	-	-	-	-
	-	-	-	-	-

▣ Maximum Ratings


Input Power Handling	5Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

▣ Dimension



▣ PCB Layout



For product information and a complete list of distributors, please go to our website

[www.zenix08.com](http://www.zenix08.com)


address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954

Tel : +82-31-8025-7100

Fax : +82-31-8025-7200

▣ Typical Performance Data at 25°C

- Insertion Loss, Ripple, Return Loss, Attenuation



- Attenuation

