


Ceramic Bandpass Filter 50Ω

ZBA-67R-2162BW14E



■ Features

- ROHS Compliant
- High power rating
- High rejection

■ Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	2162.5	-	2162.5	-	MHz
Bandwidth	14	2155.5	-	2169.5	MHz
Insertion Loss	2155.5 ~ 2169.5	-	9.0	10.0	dB
Ripple		-	1.8	2.0	dB
Return Loss		15.0	17.0	-	dB
Attenuation	2149.5	15.0	16.0	-	dBc
	2175.5	15.0	16.0	-	dBc
	-	-	-	-	-
	-	-	-	-	-
	-	-	-	-	-

■ Maximum Ratings


Input Power Handling	5Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

- Permanent damage may occur if any of these limits are exceeded.

■ Dimension



■ PCB Layout



For product information and a complete list of distributors, please go to our website

address : (Heungdeok IT Valley Tower-2111) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea 16954


Tel : +82-31-8025-7100

Fax : +82-31-8025-7200

www.zenix08.com

■ Typical Performance Data at 25°C

• Insertion Loss, Ripple, Return Loss, Attenuation



• Attenuation

