



■ Features

- ROHS Compliant
- High power rating
- High rejection

■ Pricing

Quantity	Unit Price
1 ~ 10	₩ 35,000
11 ~ 24	₩ 33,000
25 ~ 49	₩ 30,000
50 ~ 99	₩ 25,000
100 ~	₩ 19,000

■ Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	113	-	113	-	MHz
Bandwidth	10	108	-	118	MHz
Insertion Loss	108 ~ 118	-	2.5	3.0	dB
Ripple		-	0.3	0.5	dB
Return Loss		16.0	18.0	-	dB
Group Delay		-	-	-	ns
Group Delay Variation		-	-	-	ns
Attenuation	85	40.0	-	-	dB
	95	20.0	-	-	dB
	140	20.0	-	-	dB
	155~2000	40.0	-	-	dB
	-	-	-	-	dB

■ Maximum Ratings


Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

■ Dimension




■ PCB Layout



▣ Typical Performance Data at 25°C

- Insertion Loss , Ripple , Return Loss



- Attenuation

