



### ■ Features

- ROHS Compliant
- High power rating
- High rejection

### ■ Pricing

Quantity	Unit Price
1 ~ 10	₩ 35,000
11 ~ 24	₩ 33,000
25 ~ 49	₩ 30,000
50 ~ 99	₩ 25,000
100 ~	₩ 19,000

### ■ Electrical Specifications


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Center frequency	1500	-	1500	-	MHz
Bandwidth	1000	1000	-	2000	MHz
Insertion Loss	1000 ~ 2000	-	1.0	2.0	dB
Ripple		-	0.3	0.5	dB
Return Loss		15.0	18.0	-	dB
Group Delay		-	-	-	ns
Group Delay Variation		-	-	-	ns
Attenuation	DC~500	40.0	-	-	dB
	4000~6000	40.0	-	-	dB
	-	-	-	-	dB
	-	-	-	-	dB
	-	-	-	-	dB

### ■ Maximum Ratings


Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

### ■ Dimension




### ■ PCB Layout



## Typical Performance Data at 25°C

- Insertion Loss , Return Loss , Ripple , Attenuation



- Attenuation

