



### Features

- ROHS Compliant
- High power rating
- High rejection

### Pricing

Quantity	Unit Price
1 ~ 10	₩ 25,000
11 ~ 24	₩ 23,000
25 ~ 49	₩ 21,000
50 ~ 99	₩ 18,000
100 ~	₩ 13,000

### Electrical Specifications

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Cut Off frequency	300	-	300	-	MHz
Bandwidth	-	DC	-	300	MHz
Insertion Loss	DC ~ 300	-	0.5	1.0	dB
Ripple		-	-	-	dB
Return Loss		16.0	18.0	-	dB
Group Delay		-	-	-	ns
Group Delay Variation		-	-	-	ns
Attenuation	600	60.0	-	-	dB
	900	50.0	-	-	dB
	1200	50.0	-	-	dB
	1500	50.0	-	-	dB
	-	-	-	-	dB

### Maximum Ratings

Input Power Handling	3Watt max.
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 95°C

• Permanent damage may occur if any of these limits are exceeded.

### Dimension



### PCB Layout



## Typical Performance Data at 25°C

- Insertion Loss , Attenuation , Return Loss

